

FREQUENCY METER



Pointer frequency meter

90° - 250° DEFLECTION

Accuracy class: 0.5 of F_n

Measuring component: moving coil and frequency converter

Linear scale

Operating range: 0.80 Un to 1.15 Un

With additional “A” unit for 48 x 48 format with 250° and 90° if value < 100 V

Consumption: 3 VA

FEASIBILITY CONSTRAINTS

Voltage 57.7 V to 440 V and frequency 50 to 400 Hz

Deflection		90°	
		72 x 72	96 x 96
Format	Measurement range		
100 V	45-55 Hz	■	■
	55-65 Hz	■	■
230 V	45-55 Hz	■	FA90 0681
	55-65 Hz	■	■
400 V	45-55 Hz	■	FA90 0682
	55-65 Hz	■	■

Deflection		250°	
		72 x 72	96 x 96
Format	Measurement range		
100 V	45-55 Hz	■	■
	55-65 Hz	■	■
230 V	45-55 Hz	■	■
	55-65 Hz	■	■
400 V	45-55 Hz	■	■
	55-65 Hz	■	■

CUSTOMIZED PRODUCT

	Deflection	Format	Voltage	Measurement range
Examples	90°	72 x 72	100 V	45-55 Hz
	250°	96 x 96	110 V	45-65 HZ

ASSOCIATED PRODUCTS



Accessories

Seal, ring fastener, dial, sleeve, etc.
page 223